BEST ACCESS DOORS


Best Access Doors


SUBMITTAL / TECHNICAL DATA SHEET

GFRG/GFRC ACCESS PANEL FOR CEILINGS & WALLS

HINGED RADIUS CORNER

INSTALLATION SPECIFICATION






Designed for both wall and ceiling applications, the hinged **Seamless™** Panel by **BestAccessDoors** can be used where a locked door is needed but style must still be maintained. The hinged panel is great for use in ceiling applications where there is no space to push a door up and in wall applications when access to plumbing and electrical is needed

DIMENSION AND APPEARANCE

STOCK #	ACCESS DOOR OPENING SIZE	ROUGH OPENING SIZE
HG-RC-580008	8" x 8"	14" x 14"
HG-RC-580009	9" x 9"	15" x 15"
HG-RC-580012	12" x 12"	18" x 18"
HG-RC-580016	16" x 16"	22" x 22"
HG-RC-580018	18" x 18"	24" x 24"
HG-RC-580020	20" x 20"	26" x 26"
HG-RC-580024	24" x 24"	30" x 30"
HG-RC-580030	30" x 30"	36" x 36"
HG-RC-580036	36" x 36"	42" x 42"
HG-RC-580042	42" x 42"	48" x 48"
HG-RC-580048	48" x 48"	54" x 54"
HG-RC-581216	12" x 16"	18" x 22"
HG-RC-581224	12" x 24"	18" x 30"



* NEOPRENE GASKET AVAILABLE UPON REQUEST

TECHNICAL DATA					
Shell Thickness	1/8" to 3/16"				
Fastener Test Pull Out (wood stud)	525 lb avg.				
Fastener Test Pull Out (metal stud)	215 lb avg.				
Fastener Push Through Test	350 lb avg.				
Fuel Contribution (ASTM E84-80)	0				
Flame Spread (ASTM E84-80)	0				
Smoke Index (ASTM E84-80)	0				
Combustion (ASTM E84-80)	Non-combustible				
Class A non-rated	-				
CSI Code	CSI #08310				

PRODUCT FEATURES

CREATING SEAMLESS SOLUTIONS

Seamless™ Access Panels by BestAccessDoors are manufactures direct, manufactured from GFRG/GFRC & 70% post-consumer recycled glass, for a unique GREEN design-matrix designed to blend seamlessly into your walls and ceilings. They consist of a surround frame and either a drop-in door or hinged door. Available in Sixty standard residential or commercial sizes, <code>8estAccessDoors</code> panels are perfect for jobs where access is required at regular intervals. Lightweight and easily textured, the panels can be used in both new and retrofit construction across unlimited applications. Their smart design to helps contractors work smarter, faster and better, the Seamless™ panels feature a tapered edge for tape joints and won't shrink, crack or sag. Seamless™ Access Panels provide an aesthetically pleasing solution for a more attractive interior.

ADDRESS: 427 N Tatnail St,#76520 Wilmington, DE 19802-2230

PRODUCT FEATURES

- Tapered edge for tape joint
 Easily textured
- Lightweight
- · Single trade installation
- No shrinking, cracking, sagging or rusting
- Blends seamlessly into surrounding drywall
- Concealed hinge
- Reduce labor costs
- Moisture resistant
- · Zero mold & fungus growth



LEED ready





PROJECT DATA	QTY	W	Н	OPTIONS	
PROJECT NAME:					
ARCHITECT:					
DEALER:					
CONTRACTOR:	SPECIAL INSTRUCTIONS:				
LOCATION:					
DATE:	SUBMITTAL APPROVAL: (signature or stamp)				

TAGGING INSTRUCTIONS:

Tel.: 1-800-483-0823

fax: 1-888-828-6021

www.bestaccessdoors.com sales@bestaccessdoors.com