

APPLICATION

This Adjustable Z- Blade Louver with Fusible Link is Ideal for Use in Fire Doors up to 1-1/2 Hour Rating. Ideal for Installation in Existing Door

SPECIFICATIONS

MATERIAL: 18 gauge (.048") CRS frame. Min size 10" W x 6" H, Max 24" W x 24" H.

CONSTRUCTION: Louver: Z-blade louvers riveted to operating bar and frame at 1" intervals to welded 1-9/16" deep frame. Mechanical stop 5/8" x 3/8" x 16 ga. (.048") holds blades open.

Frame: Mitered and welded corners; screws fastened through prepared frame into louver core leaving corridor side of frame free of fasteners.

OPERATION: Adjustable blades of 16 gauge (.059") CRS pivot on cadmium-plated steel rivets. The blades are operated by a manual adjusting lever. A spring loaded fusible link mechanism is incorporated into the design. Upon melting of the link at 165° F, the action bar is actuated, thereby closing and locking all of the blades.

DOOR: For 1-3/4" steel or composite doors.

FASTENERS: #8 x 3/4" Phillips flathead screws to match finish.

FREE FLOW AREA: 45% free area.

For a complete list of options visit www.BestAccessDoors.com

Scan or (m) Click

SKU: BA-DLFRZ-G

FIRE-RATED ADJUSTABLE Z-BLADE LOUVER

TECHNICAL DATA SHEET



■ DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

LISTINGS & RATINGS:


Fire Ratings with UL & WHI Classification Marks Tested & Listed for UL10C, and classified in accordance with UBC7-2-94, ASTM E152, CAN/ULC S104, NFPA 252. Install in accordance with NFPA80.

Model BA-DLFRZ-G is Rated for use in fire doors up to 1-1/2 hour rating. Louver size shall not exceed maximum of 576 sq. inches, 24"W and 24" H. The minimum width and height shall not be less than 10" and 6", respectively. Louvers may be provided for classified hollow metal type and composite type

Consult with the Local Authority Having Jurisdiction (AHJ) to determine appropriate standards. Louver frame will be labeled with Listing mark.







PROJECT DATA

Custom Sizes & Options Available - Fast!

PROJECT NAME:	QTY	W	Н	OPTIONS
ARCHITECT:				
DEALER:				
CONTRACTOR:				
LOCATION:	SPECIAL INSTRUCTIONS:			
DATE:				
TAGGING INSTRUCTIONS:	SUBMITTAL APPROVAL : (signature or stamp)			



To view Pricing and Additional Product Info.



TELEPHONE: 1-800-483-0823 FAX: 1-888-828-6021



228 PARK AVE. S. #76520 NEW YORK, NY, 10003



WEBSITE:

www.BestAccessDoors.com