



Quality Access Doors - FAST!

SUBMITTAL/TECHNICAL DATA SHEET

DESCRIPTION

A premium flush mount access panel cover for a 14"x14" drywall opening. This cover can also be used on a wall or ceiling and yields a 12.375"x12.375" accessible area.

APPLICATION

- Designed for 1/2" and 5/8" thick drywall.
- Suitable for both wall and ceiling installation.
- Screws on to the face of your drywall.
- Once finished seaming over the flange, the product is ready to be primed and painted to your wall colour.
- The inserts comes primed white and ready for your paint colour.

FEATURES

- Magnetic removable triple fibre reinforced cement board cover.
- 24 gauge galvanized satin coat steel frame complete with a beaded edge and adjustable diffuser.
- 4 rare earth magnets (0.375" diameter x 0.060" thick).
- Easy installation, primed and ready to paint.
- 20 Degree angled slots for directional venting and to hide a fan.
- Fire Rated, non-flammable.
- Impact Resistant.
- Moisture and Water Resistant, Mold Resistant.
- Eco-Friendly Manufacturing and Non-Hazardous.

SPECIFICATIONS

- Over 153.14 square inches (988 square centimeters) of accessible area.
- Overall dimensions are 16.375" x 16.375" x 0.5" (415.9mm x 415.9mm x 12mm).
- Product weight is 3.6 pounds (1.64 kilograms)

SKU: **BA-IG14**



REMOVABLE FLUSH ACCESS PANEL COVER

MAGNETIC



DIMENSIONS AND APPEARANCE

>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)



Material Information:

- Raw Material:** Cement, fibres, quartz sand, non-hazardous fillers.
- Density:** 1.0 $D \le 1.2 \text{ g/cm}^3$
- Asbestos Content:** 100% asbestos-free
- Fire resistance:** Non-combustible edge and adjustable diffuser.
- Water Absorption:** $\le 40\%$
- Resistant Bending Strength:** $\le 10.5 \text{ MPa dry}$
- Moisture Movement:** 0.25 %
- Freeze Thaw:** No distortion after 25 repeated cycles of freezing and thawing .

For a complete list of options visit www.BestAccessDoors.com

PROJECT DATA

Custom Sizes Available - Fast!

Scan or Click



To view Pricing and Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :	SUBMITTAL APPROVAL :			
TAGGING INSTRUCTIONS :	(signature or stamp)			

TELEPHONE:
1-800-483-0823
FAX:
1-888-828-6021



228 PARK AVE. S. #76520
NEW YORK, NY, 10003



WEBSITE:
www.BestAccessDoors.com
E-MAIL:
info@bestaccessdoors.com